



# Installation Instructions

## CLUB CAR DS– Hinged Windshield

1982-1999

---

### Hardware Included:

- (4) Silver Aluminum Clips
- (2) “L” Shaped Rubber Clips

- (2) Duck Bill Hold Downs
- (2) Black Pop Rivets
- (4) Clear Rubber Bump-ons

### Club Car DS or any Club Car with Aluminum Frame:

1. Place two silver aluminum clips on bottom of front frame with short leg facing front of car, approximately 24 inches apart.
2. Peel protective paper from windshield and place bottom of windshield in the two silver aluminum clips. Make sure the windshield is seated in clips.
3. Place one silver aluminum clip on each side of the windshield frame directly above the hinge. Then slide the clips down the post over the windshield. Apply pressure to each clip.
4. Fold top half of windshield up so that it is resting against the frame. Take “L” shaped rubber clips and locate short side (the side with the drilled hole) to the frame and long side of the rubber clips on windshield approximately 2” from top of windshield and drill two 5/32” diameter holes through the rubber clips and into the frame. Use the two black pop rivets to secure the rubber clips to the frame. (Do this procedure on each side of the upper half of the windshield.)
5. Release the clips and place a rubber bump-on on the windshield between the windshield and post, one above the rubber clip and one below the rubber clip. With the windshield up this will add pressure to the rubber clip for a tight fit.
6. Take the two “duck bill” hold downs and place one on each side of the upper half of the windshield approximately 24 inches apart with the 1/2” leg up. Peel off the protective tape and allow the windshield to close on the bottom half of the windshield.