



Installation Instructions

Club Car Hinged Windshield and Zipper Enclosure

1. Remove the nut and bolt from each side of the lower windshield frame support bracket.
2. Set the windshield in the aluminum brackets and push down on the windshield until the windshield "bottom" is in the brackets.
3. Place a piece of extrusion (with the hole and "C" section) directly below the hinges on each side of the windshield.
4. Next press the extrusion over the windshield frame so that the holes in the extrusion and the hole in the frame line up. ("C" section on the outside)
5. Replace the bolts through the extrusion and the frame and tighten.
6. Place a piece of extrusion (with no windshield clip) over the top half of the windshield frame. ("C" section on the outside)
7. The windshield and extrusion should now be affixed to the windshield frame.
8. Mount the "hold-up" rubbers to the windshield frame and the "hold-down" pieces to the bottom half of the windshield.
9. Lay the folded enclosure on the golf car top and unfold. Drop the enclosure down on all sides and unzip the zippers. Feed the front bead (1/2 of front zipper) down through the "C" section until it is fully extended, do this to both sides of the windshield.
10. Zip the zipper to fit.
11. You have now installed the finest golf car windshield and all-weather enclosure available to the golf car market. Thank you for your purchase!

** Note: The bead will always stay in the extrusion.*