



Installation Instructions

CLUB CAR - Hinged Windshield

with Aluminum Clip

1. Place two (2) aluminum clips on bottom of front frame with short leg facing front of car, approximately 24 inches apart.
2. Peel protective paper from windshield and place bottom of windshield in the two (2) aluminum clips. Make sure the windshield is seated.
3. Place one aluminum clip on each side of the windshield directly below the hinge. And then affix to the windshield frame. Apply pressure to each clip. (It may be necessary to slide clip to windshield frame.)
4. Fold top half of windshield up so that it is resting against windshield frame. Take rubber clips and locate short side to the windshield frame and long side on windshield and drill two (2) 5/32 diameter holes through rubber clips and into the windshield frame. Using two (2) of the self-tapping screws (supplied with windshield clips) screw them through the rubber clips and into the windshield frame. (do this procedure on each side of the upper half of the windshield approx two (2) Below the hinge in the windshield
5. Next release the clips and place a rubber *bump-on* on the windshield side next to the frame, one above the rubber clip and one below the rubber clip. With the windshield up this will add pressure to the rubber clip for a tight fit.
6. Next take the two (2) duck bill hold downs and place one on each side of the upper half of the windshield approx. 24 inches apart. Peel off the protective tape and allow the windshield to close on the bottom half of the windshield